

**Features:**

- Intended for general purpose applications and may be installed in conduit, duct, or other recognized raceways in wet or dry locations
- UL listed and CSA certified
- ROHS compliant

Construction:

- The insulation is a high quality, heat and moisture resistant polyvinyl chloride compound over which a heat and light stabilized nylon jacket is tightly applied.

Related Products:

- Ground Bars, Ground Lugs

Part #	Description	Spool Size	Weight
6G-100	6 AWG Green THHN	100'	10.0 lb
6G-250	6 AWG Green THHN	250'	25.0 lb
6G-500	6 AWG Green THHN	500'	50.0 lb
2S-100	2 Solid Tinned	100'	21.0 lb
2S-250	2 Solid Tinned	250'	50.0 lb
2S-500	2 Solid Tinned	500'	100.0 lb
2G-100	2 AWG Green THHN	100'	29.0 lb
2G-250	2 AWG Green THHN	250'	64.0 lb
2G-500	2 AWG Green THHN	500'	127.0 lb
2T-100	2 AWG Tinned Green THW-2 AT&T CEQ.15540 (sold per ft)	100'	25.0 lb
2T-250	2 AWG Tinned Green THW-2 AT&T CEQ.15540 (sold per ft)	250'	63.0 lb
2T-500	2 AWG Tinned Green THW-2 AT&T CEQ.15540 (sold per ft)	500'	126.0 lb