

Product Overview

Hoisting grips are used to support the weight of vertical cable runs.

- Closed style allows simplified installation, simply slip on to the cable
- Stainless steel braided wire construction
- Use at top of cable before installing connector



Product Family

SKU	Cable Size & Type	Overall Length	Mesh Length	Max Interval (Cable Wt <2 lb/ft)	Max Interval (Cable Wt >2 lb/ft)	Max Cable Load	Weight
HG38-C	3/8" Coax & Stranded 10mm Cable & 3/8" Flex, & RG11U	11"	6"	200'	150'	100 lbs	0.05
HG12-C	1/2" Coax & Stranded 15mm & 1/2" Cable	18"	7"	200'	150'	150 lbs	0.10
HG58-C	5/8" Coax & Stranded 22mm & 7/8" Cable	25"	14"	200'	150'	250 lbs	0.50
HG78-C	7/8" Coax & Stranded 30mm & 1-1/4" Cable	34"	21-1/2"	200'	150'	400 lbs	0.50
HG114-C	1-1/4" Coax & Stranded 42mm & 1-5/8" Cable	40"	27"	200'	150'	475 lbs	0.40
HG158-C	1-5/8" Coax	45"	30"	200'	150'	475 lbs	0.60
HG214-C	2-1/4" Coax	45"	30"	200'	150'	475 lbs	0.95

Warning

Never exceed the maximum load rating or the maximum interval per grip specified in the table above. Please contact technical support for additional assistance.