





THE MAXIMUM TAPER ADJUSTMENT IS 5.7° BASED UPON 30" SPACING OF ADJUSTABLE MOUNTING BRACKETS.

THE MAXIMUM TAPER ADJUSTMENT IS 3.8° BASED UPON 45" SPACING OF ADJUSTABLE MOUNTING BRACKET.

## **TOLERANCE NOTES**

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWED, SHEARED AND GAS CUT EDGES (\$ 0.030") ORILLED AND GAS CUT HOLES (\$ 0.030") - NO CONING OF HOLES LASER CUT EDGES AND HOLES (\$ 0.010") - NO CONING OF HOLES

BENDS ARE ± 1/2 DEGREE ALL OTHER MACHINING (± 0.030")

ALL OTHER ASSEMBLY (± 0.060")

PROPRIETARY MOTE:
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT
INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF
VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

## DESCRIPTION

**R5 UNIVERSAL PIPE MOUNT KIT** 

WITH 4-1/2" PIPE



Engineering Support Team: 1-888-753-7446

Locations: New York, NY Atlanta, GA Los Angeles, CA Plymouth, IN Dallas, TX

CPD NO.		DRAWN BY	ENG. APPROVAL	PART NO.	
4718		RH18 3/29/2010		R5	- 
CLASS	SUB	DRAWING USAGE	CHECKED BY	DWG. NO.	ן ייין
81	01	CUSTOMER	BMC 11/12/2015	R5	_