


NOTE: MAX TORQUE 35 LB-FT PER BOLT

PARTS LIST						
ITEM	QTY	PART NO.	PART DESCRIPTION	LENGTH	UNIT WT.	NET WT.
1	1	X-SOCX3	3" STANDOFF CROSSOVER WELDMENT		7.22	7.22
2	2	X-SO12-CLS	V-CLAMP FOR 0.5" HARDWARE	7 9/16 in	3.33	6.66
3	8	G12065	1/2" x 6-1/2" HDG HEX BOLT GR5 FULL THREAD	6 1/2 in	0.41	3.28
4	8	G12FW	1/2" HDG USS FLATWASHER	3/32 in	0.03	0.27
5	8	G12LW	1/2" HDG LOCKWASHER	1/8 in	0.01	0.11
6	8	G12NUT	1/2" HDG HEAVY 2H HEX NUT	7/8 in	0.07	0.57
					TOTAL WT. #	17.89



FINISH:
HOT DIP GALVANIZED.

					TOLERANCE NOTES TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030''$) DRILLED AND GAS CUT HOLES ($\pm 0.030''$) - NO CONING OF HOLES LASER CUT EDGES AND HOLES ($\pm 0.010''$) - NO CONING OF HOLES BENDS AND ANGLES ARE $\pm 1/2$ DEGREE ALL OTHER MACHINING ($\pm 0.030''$) ALL OTHER ASSEMBLY ($\pm 0.060''$)		DESCRIPTION 3" UNIVERSAL STANDOFF CROSSOVER KIT			SITE PRO 1 Engineering Support Team: sp1engineering@valmont.com A valmont COMPANY				
B	REPLACED G1206 WITH G12065			SP1	SDR	3/30/2026	CPD NO.	DRAWN BY	ENG. APPROVAL	PART NO.	PAGE 1 OF 1			
A	REVISED X-SOCX3 AND CHANGED TO 1/2" HW			SP1	SDR	8/4/2025	PATENT INFORMATION: WWW.SITEPRO1.COM/PATENTS		SP1	KS		4/4/2024	9/18/2025	SOCX3-U
REV	DESCRIPTION OF REVISIONS			CPD	BY	DATE	PROPRIETARY NOTE: THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.	CLASS	SUB	DRAWING USAGE		CHECKED BY	DWG. NO.	SOCX3-U
REVISION HISTORY														