





## **TOLERANCE NOTES**

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWED, SHEARED AND GAS CUT EDGES ( $\pm\,0.030$ ") DRILLED AND GAS CUT HOLES (± 0.030") - NO CONING OF HOLES LASER CUT EDGES AND HOLES (± 0.010") - NO CONING OF HOLES BENDS ARE ± 1/2 DEGREE

ALL OTHER MACHINING (± 0.030")

ALL OTHER ASSEMBLY (± 0.060")

PROPRIETARY NOTE:
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT
INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF
VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION **QUAD UNIVERSAL RING MOUNT** FOR POLES 12" TO 60" (UQB4)

A valmont ♥ common

Engineering Support Team: 1-888-753-7446

Locations: New York, NY Atlanta, GA Los Angeles, CA Plymouth, IN Salem, OR Dallas, TX

CPD N	Ο.	DRAWN BY		ENG. APPROVAL		PART NO.
4893		CEK	CEK 9/20/2010			UQB4
CLASS	SUB	DRAWING	USAGE	CHECKED	BY	DWG. NO.
81	01	CUS	STOMER	вмс	9/20/2010	UQB4

Α UQB4 revised to meet modern loading 4863 | JET | 6/3/2019 REV CPD BY **DESCRIPTION OF REVISIONS** DATE **REVISION HISTORY**