

Product Overview

This hot-dip galvanized steel pipe is available in both Schedule 40 and Schedule 80 wall thicknesses, covering a wide range of outside diameters and lengths.

- Plain-end pipe with no threading
- Factory cut ends for consistent lengths
- Outside diameters ranging from 2-3/8" up to 4-1/2"
- Standard lengths from 5' up to 21'
- Manufactured to ASTM A53 Grade B specifications
- Steel strength: Yield Fy = 35 ksi [240 MPa] / Tensile Fu = 60 ksi [415 MPa]
- Hot-dip galvanized finish in accordance with ASTM A123 requirements
- Other sizes available upon request, please inquire



Product Family

SKU	Outer Diameter (OD) (in)	Length (in)	Schedule	Weight
P2108	2-3/8	108	40	34.00
P2120	2-3/8	120	40	37.00
P2132	2-3/8	132	40	40.00
P2156	2-3/8	156	40	43.00
P2180	2-3/8	180	40	55.00
P2252	2-3/8	252	40	77.00
P2252-80	2-3/8	252	80	106.00
P260	2-3/8	60	40	17.40
P263	2-3/8	63	40	18.25
P272	2-3/8	72	40	23.00
P284	2-3/8	84	40	26.00
P296	2-3/8	96	40	27.80
P30108	2-7/8	108	40	55.00
P30120	2-7/8	120	40	60.00
P30126	2-7/8	126	40	64.00
P30156	2-7/8	156	40	78.00
P30180	2-7/8	180	40	90.00
P30252	2-7/8	252	40	122.00
P30252-80	2-7/8	252	80	170.00
P3072	2-7/8	72	40	35.00
P3084	2-7/8	84	40	41.00
P3096	2-7/8	96	40	49.00

Product Family (Continued)

SKU	Outer Diameter (OD) (in)	Length (in)	Schedule	Weight
P3108	3-1/2	108	40	66.00
P3120	3-1/2	120	40	80.00
P3156	3-1/2	156	40	92.00
P3252-80	3-1/2	252	80	217.00
P360	3-1/2	60	40	38.00
P372	3-1/2	72	40	47.00
P384	3-1/2	84	40	53.20
P396	3-1/2	96	40	60.80
P4126	4-1/2	126	40	106.00
P4252	4-1/2	252	40	249.00
P472	4-1/2	72	40	65.00