


Product Overview

This junction provides a 90° branch connection where three cable tray runs meet, maintaining continuous cable support through the intersection.

- Extruded aluminum alloy 6063 construction
- 1.13" wide tubular rungs, arc-welded on both sides
- Class 3 fitting with 2.375" flanges
- 3" flat side rail tangents beyond the curvature
- Each section includes splice plates and fastening hardware
- Splice resistance less than 0.00033 ohms
- UL Classified as an equipment grounding conductor per NEC 392
- Compliant with NEMA VE1, CSA C22.2 No. 126, and NEC Article 392
- Matching covers listed below



Additional Images



Product Family

SKU	Size	Type	Pairs With	Bend Radius	End Widths (W1xW2)	Weight
LT-TJ-06-4D	6"	Tray	LT-VTJ-06-A	12"	36" x 21"	8.00
LT-TJ-09-4D	9"	Tray	LT-VTJ-09-A	12"	39" x 24"	9.00
LT-TJ-12-4D	12"	Tray	LT-VTJ-12-A	12"	42" x 27"	10.00
LT-TJ-18-4D	18"	Tray	LT-VTJ-18-A	12"	48" x 33"	11.35
LT-TJ-24-4D	24"	Tray	LT-VTJ-24-A	12"	54" x 39"	13.00
LT-VTJ-06-A	6"	Cover	LT-TJ-06-4D	-	-	6.00
LT-VTJ-09-A	9"	Cover	LT-TJ-09-4D	-	-	6.50
LT-VTJ-12-A	12"	Cover	LT-TJ-12-4D	-	-	7.00
LT-VTJ-18-A	18"	Cover	LT-TJ-18-4D	-	-	7.60
LT-VTJ-24-A	24"	Cover	LT-TJ-24-4D	-	-	8.00