




Product Overview

These straight aluminum ladder sections support rooftop cable runs, forming the main lengths between fittings in any tray layout.

- 5" side rails with 4" loading depth
- 9" rung spacing, 16 rungs per section
- 3/4" lip on both sides of the tray
- Each 12' section includes splice plates and hardware
- Load and deflection data tested per NEMA VE1 and CSA C22.2 No. 126, witnessed and certified by Underwriters Laboratories (UL file E341872)
- Matching cover listed below
- Ships from select locations



Additional Images



Product Family

SKU	Width (W)	Length	Type	Pairs With	Rung Safe Load, Uniform	Weight
LT-06-4D	6"	12'	Tray	LT-VSS-06-A	2,400 lbs	15.00
LT-09-4D	9"	12'	Tray	LT-VSS-09-A	1,600 lbs	17.00
LT-12-4D	12"	12'	Tray	LT-VSS-12-A	1,200 lbs	19.00
LT-18-4D	18"	12'	Tray	LT-VSS-18-A	800 lbs	22.00
LT-24-4D	24"	12'	Tray	LT-VSS-24-A	600 lbs.	23.00
LT-VSS-06-A	6"	12'	Cover	LT-06-4D	-	5.00
LT-VSS-09-A	9"	12'	Cover	LT-09-4D	-	7.00
LT-VSS-12-A	12"	12'	Cover	LT-12-4D	-	8.00
LT-VSS-18-A	18"	12'	Cover	LT-18-4D	-	11.00
LT-VSS-24-A	24"	12'	Cover	LT-24-4D	-	15.00